







CODE													
	BAR	DROP	l/min	4 km/h	6 km/h	8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h	20 km/h	l/ha @ 60m/min (3.6km/h)
HCF80015	2	F	0.49	147	98	73	59	49	42	37	33	29	163
	3	F	0.60	180	120	90	72	60	51	45	40	36	200
	4	F	0.69	208	139	104	83	69	59	52	46	42	231
	5	F	0.77	232	155	116	93	77	66	58	52	46	258
	6	F	0.85	255	170	127	102	85	73	64	57	51	283
	7	VF	0.92	275	183	137	110	92	79	69	61	55	306
	8	VF	0.98	294	196	147	118	98	84	73	65	59	327
	9	VF	1.04	312	208	156	125	104	89	78	69	62	346
	10	VF	1.10	329	219	164	131	110	94	82	73	66	365
	HCF8002	2	M	0.65	196	131	98	78	65	56	49	44	39
3		F	0.80	240	160	120	96	80	69	60	53	48	267
4		F	0.92	277	185	139	111	92	79	69	62	55	308
5		F	1.03	310	207	155	124	103	86	77	69	62	344
6		F	1.13	339	226	170	136	113	97	85	75	68	377
7		F	1.22	367	244	183	147	122	105	92	81	73	407
8		F	1.31	392	261	196	157	131	112	98	87	78	435
9		F	1.39	416	277	208	166	139	119	104	92	83	462
10		VF	1.46	438	292	219	175	146	125	110	97	88	487
HCF8003		2	M	0.98	294	196	147	118	98	84	73	65	59
	3	M	1.20	360	240	180	144	120	103	90	80	72	400
	4	F	1.39	416	277	208	166	139	119	104	92	83	462
	5	F	1.55	465	310	232	186	155	133	116	103	93	516
	6	F	1.70	509	339	255	204	170	145	127	113	102	566
	7	F	1.83	550	367	275	220	183	157	137	122	110	611
	8	F	1.96	588	392	294	235	196	168	147	131	118	653
	9	F	2.08	624	416	312	249	208	178	156	139	125	693
	10	F	2.19	657	438	329	263	219	188	164	146	131	730
	HCF8004	2	C	1.31	392	261	196	157	131	112	98	87	78
3		M	1.60	480	320	240	192	160	137	120	107	96	533
4		M	1.85	554	370	277	222	185	158	139	123	111	616
5		M	2.07	620	413	310	248	207	177	155	138	124	689
6		F	2.26	679	453	339	272	226	194	170	151	136	754
7		F	2.44	733	489	367	293	244	209	183	163	147	815
8		F	2.61	784	523	392	314	261	224	196	174	157	871
9		F	2.77	831	554	416	333	277	238	208	185	166	924
10	F	2.92	876	584	438	351	292	250	219	195	175	974	

Classification according to ASABE S572.3 and ISO25358

	DROP SIZE RATING
VF	Very fine
F	Fine
M	Medium
C	Coarse

For further product information please call The Technical Team on 01522 246491.

Agrigem Ltd • Riverside Enterprise Park • Skellingthorpe Road • Saxilby • Lincoln • LN1 2FU

www.agrigem.co.uk